



ISO 8217 2010 FUEL STANDARD FOR MARINE DISTILLATE FUELS

MARINE DISTILLATE FUELS

Limit	Parameter	DMX	DMA	DMZ	DMB
Max.	Viscosity at 40°C (mm ² /s)	5.500	6.000	6.000	11.00
Min.	Viscosity at 40°C (mm ² /s)	1.400	2.000	3.000	2.000
Max.	Micro Carbon Residue at 10% Residue (% m/m)	0.30	0.30	0.30	-
Max.	Density at 15°C (kg/m ³)	-	890.0	890.0	900.0
Max.	Micro Carbon Residue (% m/m)	-	-	-	0.30
Max.	Sulphur (% m/m)	1.00	1.50	1.50	2.00
Max.	Water (% V/V)	-	-	-	0.30
Max.	Total sediment by hot filtration (% m/m)	-	-	-	0.10
Max.	Ash (% m/m)	0.010	0.010	0.010	0.010
Min.	Flash point (0°C)	43.0	60.0	60.0	60.0
Max.	Pour point in Summer (0°C)	-	0	0	6
Max.	Pour point in Winter (°C)	-	-6	-6	0
Max.	Cloud point (°C)	-16	-	-	-
Min.	Calculated Cetane Index	45	40	40	35
Max.	Acid Number (mgKOH/g)	0.5	0.5	0.5	0.5
Max.	Oxidation stability (g/m ³)	25	25	25	25
Max.	Lubricity, corrected wear scar diameter (wsd 1.4 at 60°C) (um)	520	520	520	520
Max.	Hydrogen sulphide (mg/kg)	2.00	2.00	2.00	2.00
	Appearance	Clear & Bright			-

The above is a service for informational purposes only. Fix Energies assumes no responsibility for any errors or omissions.